

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/049453 A1

(51) International Patent Classification?: B65G 1/00, E01F
15/14, A47B 96/00, 47/00, E02B 3/26

(21) International Application Number:
PCT/AU2004/001595

(22) International Filing Date:
18 November 2004 (18.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003906339 18 November 2003 (18.11.2003) AU

(71) Applicant (for all designated States except US): INNOVA-
TION CENTRAL PTY LTD [AU/AU]; 1/157 Sir Donald
Bradman Drive, Hilton, South Australia 5033 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HUXTABLE, Paul,

Stewart [AU/AU]; 55 Annesley Avenue, Trinity Gardens,
South Australia 5069 (AU). PENDERGRAST, Ian,
Howard [AU/AU]; 2 Nyrang Court, Woodcroft, South
Australia 5162 (AU).


(74) Agent: PHILLIPS ORMONDE & FITZPATRICK; 367
Collins Street, Melbourne, Victoria 3000 (AU).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: RESILIENT PROTECTOR TO PROTECT A STRUCTURE FROM AN IMPACT



(57) Abstract: The invention relates to a protecting apparatus (10) for protecting a structure (100) from an impact. The protecting apparatus (10) is arranged to be mounted on the structure (100) and includes a bumper member (12), a structure positioning member (14) and at least one resiliently flexible joining portion (16). The structure positioning member (14) is arranged in use to be positioned in contact with or adjacent to a portion of the structure (100) being protected. The at least one resiliently flexible joining portion (16) extends between the bumper member (12) and the structure positioning member (14) so that when an outer surface (12a) of the bumper member (12) is impacted, the impact force is dissipated at least in part by flexure of the at least one joining portion (16).



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report